
GLOBAL SALES NETWORK

ELECTRIC TOW TRACTOR

10-15t















ISO14001: 2004

ISO9001: 2008

HANGCHA GROUP CO., LTD.

(Zhejiang Hangcha Imp.&Exp.Co.,ltd.)

E-mail: whsales@hcforklift.com sales@hcforklift.com



Forward/Reverse inching switch and emergency switch are mounted on the left rear, them make the hook easy



The large internal space is easy for maintenance



Side-exchange battery design is convenient for changing battery.



The battery cover can be fully opened, the design is easy

Appearance

■ Body choosing modern large circular arc streamline surface modeling,is in accordance with international design trend.

Reliability

■ The battery is dropped down to the lowest part of frame, this gives the tractor excellent stability because low center of gravity.

Comfort

- Low noise, low shake, energy efficient, environmental protection.
- Low step and capacious room will be much appreciated by operator who have to get on and off
- Ergonomically design switch instrument and pedal. Adjustable steering wheel and seat ensure driver maximum comfortable and minimum fatique.
- Full hydraulic steering system, the steering is easy.
- Large-capacity of the container making the operation more flexible and convenient.

Advance

- New AC system provide more power, more precise performance of speed control, more safety and reliability, regenerative system.
- High effective AC system prolong the working time.
- Adopt the international first-class brand of LCD ,with the battery indication,fault self-diagnosis table and accurately display in the harsh environment function.
- Rich visual sense improve the productivity.
- Exchange battery is easy because the design of side-exchange battery.

Easy maintain

■ You can open and close the battery cover hood for daily checkup the battery, motor and controller. It's easy to access inner of battery cover for maintenance.

Advantage of AC system

Multiple benefits of the AC Power System include:fast response to operating commands, precise power control, regenerative system.

- Economy of operation, resulting from minimized maintenance costs,e.g.
- A high number of work cycles can be obtained from each battery charge due to the efficiency of the system of energy control.
- System is fully adjustable to suit the load, working area and operator. Inbuilt diagnostics record intermittent faults and service requirements reducing expensive service time.

Standard Feature

- Head lamp
- Turning lamp
- Rear combined LED
- Horn
- Emergency disconnect switch
- Inching function
- AC Power System
- Standard battery
- Large LCD display
- Pneumatic tyre

10-15t electric tow tractor specification

	Manufacture				HANGCHA		
Specification							
	Model				QSD10-C1	QSD15-C1	
	Operation				Seated	Seated	
Performance	1	Towed I	oad capacity	Kg	10000	15000	
	2	Rated drawbar pull(60min)		Kg	250	375	
	3	Max.Drawbar pull(5min)		Kg	800	1100	
	4	Travel speed with rated load		Km/h	10	10	
	5	Travel speed without load		Km/h	18	18	
	6	Gradeability without load		%	25	25	
	7	Turning radius		mm	1985	2170	
Dimensions	8	Overall length		mm	2122	2322	
	9	Width		mm	1100	1100	
	10 Height	11.7.66	Without cab(Std)	mm	1440	1440	
		Height	with cab(Option)	mm	2112	2112	
	11	Wheel base		mm	1200	1400	
	12	710000	Front	mm	897.5	897.5	
	13	13 Thread	Rear	mm	908	908	
	14	Ground clearance		mm	100	100	
	15	Towing coupling height		mm	350/450	350/450	
	16	Sevice weight		Kg	2200	2450	
Tyre	17	Front wheels/number			5.0-8/2	5.0-8/2	
	18	Rear wheels/number			6.0-9/2	6.0-9/2	
Drive	19	Battery		A.H	420	450	
	20	Voltage		V	48	80	
	21	Motor		KW	AC6.8	AC11.75	

10-15t electric tow tractor performance (5 Min start on slope)

Surface condition (Dry Even Concrete)	Model	QSD10-C1	QSD15-C1
Level load		10000	15000
	1°	8500	12000
Grade (Degrees)	2°	6800	9500
(Degrees)	3°	5500	8000
	4°	4500	6800

Specifications are subject to change without notice.

Options

- Super elastic solid tyre
- High capacity import battery
- Simple cabin

- Closed cabin
- Suspension seat
- .
- Mirror

- Warning lamp
- Charger
- Customer painting
- Height of tractor pin

Dimensions

